

## RESIDENTIAL AND COMMERCIAL R32

.....

# ACTIVE LINE DC INVERTER MULTISPLIT INDOOR UNITS

Wall HKEU 203 ZL - HKEU 263-533-713 ZAL - HKEU 353 ZAL-1



Remote control  
included as  
standard

High density filter  
Self-cleaning function  
Anti-freeze function 8° C

Model			HKEU 203 ZL	HKEU 263 ZAL	HKEU 353 ZAL-1	HKEU 533 ZAL	HKEU 713 ZAL
Type	Indoor wall unit						
Control (included)	Remote control						
Rated capacity	Cooling	kW	2.10	2.60	3.50	5.30	7.00
	Heating	kW	2.30	2.90	3.80	5.60	7.30
<b>Electrical data</b>							
Power supply	Ph-V-Hz		-	-	-	-	-
Connection wires between I.U. and O.U.	no.		4	4	4	4	4
<b>Refrigerant circuit</b>							
Diameter of refrigerant piping on liquid/gas	mm (inches)		ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")	ø9.52(3/8") - ø15.88(5/8")
<b>Product specifications</b>							
Dimensions	LxDxH	mm	805x194x285	805x194x285	805x194x285	957x213x302	1040x220x327
Net weight		Kg	7.5	7.5	7.5	10	12.3
Sound pressure level	Hi/Mi/Lo/Ulo	dB(A)	40/30/26/21	40/30/26/21	40/34/26/22	44/37/30/25	44.5/42/34.5/28
Sound power level	Hi	dB(A)	54	54	53	55	59
Treated air (High / Med. / Low)		m <sup>3</sup> /h	520/460/340	520/460/340	600/500/360	840/680/540	980/817/662
Motor power (Output)		W	40	40	40	36	58
<b>Optional parts</b>							
Wi-Fi module			HKM-WiFi				
Wired remote control			NO				
Centralized control			NO				

# MULTISPLIT INDOOR UNITS

Console HFIU 260 ZL - HFIU 350 ZAL



Remote control  
included as  
standard

4 air distribution inlets for increased system energy efficiency  
Double air distribution mode  
Anti-formaldehyde filter supplied

Model			HFIU 260 ZL	HFIU 350 ZAL
Type	Indoor console unit			
Control (included)	Remote control			
Rated capacity	Cooling	kW	2.70	3.50
	Heating	kW	3.50	3.80
<b>Electrical data</b>				
Power supply	Ph-V-Hz		-	-
Connection wires between I.U. and O.U.	no.		4	4
<b>Refrigerant circuit</b>				
Diameter of refrigerant piping on liquid/gas	mm (inches)		ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")
<b>Product specifications</b>				
Dimensions	LxDxH	mm	700x600x210	700x600x210
Net weight		Kg	14.8	14.8
Sound pressure level	Hi/Mi/Lo	dB(A)	43/41.5/35	43/41.5/35
Sound power level	Hi	dB(A)	58	58
Treated air (High / Med. / Low)		m <sup>3</sup> /h	512/480/370	512/480/370
Motor power (Output)		W	67	67
<b>Optional parts</b>				
Wi-Fi module			NO	
Wired remote control			YES	
Manual centralized control	Requires NIM-GRH interface	YES		
		XRV Mobile BMS		